



BE THEIR HEALTH GUARDIAN

HK-400III VET Syringe Pump

- Compact and light weight design allow easy moving and transferring.
- Automatically identifies various syringe types and sizes from 2ml to 60ml.
- Numeric and graphic pressure indicator helps caregivers identify occlusion in advance to prevent potential risks.
- Flow rates deliver with +/- 2% accuracy as low as 0.1 mL/h.
- Long-lasting battery: the battery life is long-lasting enough to last up to 8 hours at 5ml/h.
- Advanced moisture protection(IP44) for cleaning and disinfection results in optimized stability and fewer repair costs.




Automatically identifies various syringe types and sizes from 2ml to 60ml.



Caregivers can easily install or remove pumps thanks to the integrated handle and rotatable pole clamp.



Numeric keys combines button design facilitates fast programming.



Hidden handle design helps to save room.



Model	HK-400III VET
Infusion Mode	Rate mode, Time mode, Weight mode, Intermittent mode, Drug library
Applicable syringe	Open system. 2ml,5ml, 1 0ml, 20ml, 30ml,50/60ml
Accuracy	±2%
Infusion rate	2 ml syringe: 0.1 - 150 ml/h 10 ml syringe: 0.1 - 300 ml/h 30 ml syringe: 0.1 - 900 ml/h 5 ml syringe: 0.1 - 150 ml/h 20 ml syringe: 0.1 - 600 ml/h 50 (60) ml syringe: 0.1 - 1800 ml/h
VTBI	(0-9999.99)ml
Volume infused	0-36000 ml
KVO rate	0.1~10ml/h, increment: 0.1ml/h
BOLUS rate	2 ml syringe: 0.1 - 150 ml/h 10 ml syringe: 0.1 - 300 ml/h 30 ml syringe: 0.1 - 900 ml/h 5 ml syringe: 0.1 - 150 ml/h 20 ml syringe: 0.1 - 600 ml/h 50 (60) ml syringe: 0.1 - 1800 ml/h
Occlusion pressure	13 levels
History record	50000
Alarm	Handle off, Syringe off, Empty, Occlusion, Battery exhaust, Low Battery, Near empty, Almost Done (infusion near over), Finished, Use Battery, AC fail, No Operate
Features	With KVO, Bolus,Anti-reverse detection,Double CPU,Key lock,Titration, DPS, Stackable, Standby Mode
Optional functions	Optional pole clamp for pet cage
Waterproof	IP44
Power consumption	35VA
Size	240 * 135 *138 mm (length x width x height)
Net weight	1.8KG
Power supply	AC: 100-240V 50/60Hz
Battery	DC7.2V (Rechargeable lithium polymer battery, 2550mAh or 2550mAh×2) 8h at 5ml/h(1 battery) 16h at 5ml/h(2 batteries)
Working environment	Temperature: 5°C-40°C, relative humidity: 10%-95%(no frosting)
Atmosphere pressure	86.0-106.0 kPa

hawkmed



Shenzhen Hawk Medical Instrument Co., Ltd.

+86 0755-83151901 szhk@hawkmedical.cn

www.hawkmed.com.cn

Add: 1st-4th Floor, Building C, Jianyetai Industrial Zone, No.11 Minhuan Road, Fukang Community, Longhua Street, Longhua District, Shenzhen, Guangdong, P.R. China

